

## IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

Product

Pumps (Multi-stage, centrifugal electric pumps for water supply)

Name and address of the applicant

ESPA 2025 S.L.  
Crta. Mieres s/n,  
17820 BANYOLES (GIRONA), Spain

Name and address of the manufacturer

same as applicant

Name and address of the factory

same as applicant

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

**Type 220 60:**  
220 V, ~, 60 Hz, 1500 W to 2500 W, Class I, IPX5 (MULTI), 45° C, Class F  
**Type 220/380 60:**  
220/380 V, 3~, 60 Hz, 1700 W to 15000 W, Class I, IPX5 (MULTI)  
IPX4 (VE), 45° C, Class F

Trademark (if any)

ESPA

Customer's Testing Facility (CTF) Stage used

Stage 1

Model / Type Ref.

MULTI, VE / 220 60, 220/380 60

Additional information (if necessary may also be reported on page 2)

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010(ed. 5.0) + corrigendum 2010 + Corrigendum 2 - April 2011 + A1:2013 + A2:2016,  
IEC 60335-2-41:2012(ed. 4.0)**National Differences:**  
Saudi Arabia (SA)

As shown in the Test Report Ref. No. which forms part of this Certificate

2219/0260/3

This CB Test Certificate is issued by the National Certification Body

SGS Belgium NV - Division SGS CEBEC  
Riverside Business Park  
Avenue Internationalelaan 55, Building D  
B-1070 Brussels, Belgium

Date: 22/06/2020

Signature: Daniel Arranz

## Name and address of the factories:

## Additional information:

	<b>Type: 220 60</b>
Model (s)	MULTI25 3M, MULTI25 4M, MULTI35 2M N, MULTI35 3M N, MULTI45 2M N
Parameters:	
Rated voltage	<b>220V AC 60Hz</b>
Rated power	<b>1500W - 2500W</b>
Protection class	<b>F</b>
Protection degree	<b>X5 (MULTI)</b>
Maximum temperature	<b>45°C</b>
Throughput capacity	<b>(20 – 260) l/min</b>
Minimum height	<b>10 m – 42 m</b>
Maximum height	<b>36 m – 85 m</b>

	<b>Type: 220/380 60</b>
Model (s)	MULTI35 2 N SP2, MULTI35 3 N SP1, MULTI35 4 N SP1, MULTI35 5 N SP1, MULTI35 6 N SP1, MULTI45 2 N SP2, MULTI45 3 N SP2, MULTI45 4 N SP1, MULTI45 5 N SP1, VE94 5 SP2, VE94 6 SP2, VE94 7 SP2, VE94 8, VE94 9 SP2, VE94 10, VE94 11 SP2, VE121 2 N, VE121 3 N, VE121 4 N, VE121 5 N, VE121 6 N
Parameters:	
Rated voltage	<b>220/380V 3AC 60Hz</b>
Rated power	<b>1700W – 15000W</b>
Protection class	<b>F</b>
Protection degree	<b>X5 (MULTI), X4(VE)</b>
Maximum temperature	<b>45°C</b>
Throughput capacity	<b>(30 – 600) l/min</b>
Minimum height	<b>13 m – 153 m</b>
Maximum height	<b>36 m – 159 m</b>

SGS Belgium NV - Division SGS CEBEC  
Riverside Business Park  
Avenue Internationalelaan 55, Building D  
B-1070 Brussels, Belgium




Date: 22/06/2020

Signature: Daniel Arranz