

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Pumps (Centrifugal single stage pump for water recirculation in whirlpools)

Name and address of the applicant

ESPA 2025 S.L.
Crt. Mieres s/n,
17820 BANYOLES (GIRONA), Spain

Name and address of the manufacturer

same as applicant

Name and address of the factory

same as applicant

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

~, Class I, IPX5
115 60 14821/STD: 115 V, 60 Hz, 550 W, 800 W
220 60 14286/STD: 220 V, 60 Hz, 650 W, 800 W
230 50 13934/STD: 230 V, 50 Hz, 1100 W, 1300 W
230 50 14767/STD: 230 V, 50 Hz, 700 W, 900 W

Trademark (if any)

ESPA

Customer's Testing Facility (CTF) Stage used

Stage 1

Model / Type Ref.

TIPER & TIPER 2 Series
115 60 14821/STD, 220 60 14286/STD,
230 50 14767/STD, 230 50 13934/STD

Additional information (if necessary may also be reported on page 2)

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010(ed. 5.0) + corrigendum 2010 + Corrigendum 2 - April 2011 + A1:2013 + A2:2016,
IEC 60335-2-41:2012(ed. 4.0)**National Differences:**

EU Group differences (No specific countries addressed), South Africa (ZA) and United Arab Emirates (AE).

As shown in the Test Report Ref. No. which forms part of this Certificate

2221/0006

This CB Test Certificate is issued by the National Certification Body

SGS Belgium NV - Division SGS CEBEC
Riverside Business Park
Avenue Internationalelaan 55, Building K
B-1070 Brussels, Belgium

Date: 26/08/2021



Signature: Daniel Arranz

Name and address of the factories:
Additional information:

This certificate covers the followings equipments:

	Type: 115 60 14821/STD	Type: 220 60 14286/STD
Model (s)	TIPER 70M; TIPER 90M	TIPER 70M; TIPER 90M
Parameters:		
Rated voltage	115 VAC 60Hz	220 VAC 60Hz
Rated power	550W, 800W	650W, 800W
Protection class	I	I
Protection degree	X5	X5
Max. temperature	50	50
Throughput capacity	(66-333) l/min	(66-333)l/min
Minimum height	2,5 m – 9 m	2,5 m – 9 m
Maximum height	9,5 m – 10 m	9,5 m – 10 m

	Type: 230 50 14767/STD	Type: 230 50 13934/STD
Model (s)	TIPER 70M; TIPER 90M	TIPER2 75M; TIPER 2 125M
Parameters:		
Rated voltage	230 VAC 50Hz	230 VAC 50Hz
Rated power	700W, 900W,	1100W, 1300W
Protection class	I	I
Protection degree	X5	X5
Max. temperature	50	50
Throughput capacity	(66-333) l/min	(80-430) l/min
Minimum height	2,3 m – 9 m	1 m – 13 m
Maximum height	9,6 m – 10 m	13,5 m – 15 m

For details refer to test report.

SGS Belgium NV - Division SGS CEBEC
 Riverside Business Park
 Avenue Internationalelaan 55, Building K
 B-1070 Brussels, Belgium




Date: 26/08/2021

Signature: Daniel Arranz