

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

pumps (Swimming pool pumps)

Name and address of the applicant

ESPA 2025 S.L.
Ctra. Mieres s/n,
17820 BANYOLES (GIRONA), Spain

Name and address of the manufacturer

same as applicant

Name and address of the factory

same as applicant

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

Class I, IPX5, F
Type 220 60: 220 V, ~, 60 Hz, 500 to 2700 W
Type 220/440 60: 220/440 V, 3~, 60 Hz, 800 to 2700 W
Type 230 50: 230 V, ~, 50 Hz, 200 to 2800 W
Type 230/400 50: 230/400 V, 3~, 50 Hz, 900 to 2600 W
Type 220-230 60: 220-230 V, ~, 60 Hz, 500 to 2700 W

Trademark (if any)

ESPA, ESPA LEADER

Customer's Testing Facility (CTF) Stage used

CTF Stage 1

Model / Type Ref.

**SILEN I, SILEN S, SILEN S2, NOX, SIROCCO & REPOSPPOOL
Series / 230 50, 230/400 50, 220 60, 220/440 60**

Additional information (if necessary may also be reported on page 2)

Re-issue of BE-9253/M1 dated 2021-04-07 due to technical change.
Inclusion of new derived models. For details refer to test report.
☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010(ed. 5.0) + corrigendum 2010 + Corrigendum 2 - April 2011 + A1:2013 + corrigendum 2016-05 to A2:2016 + A2:2016,
IEC 60335-2-41:2012(ed. 4.0)

National Differences:

EU Group Differences (No specific countries addressed), ZA, AE, SA

As shown in the Test Report Ref. No. which forms part of this Certificate

2119/0027-AM2, 2119/0027-AM1, 2119/0027

This CB Test Certificate is issued by the National Certification Body

SGS Belgium NV - Division SGS CEBEC
Riverside Business Park
Avenue Internationale laan 55, Building A
B-1070 Brussels, Belgium

Date: 15/10/2026


Signature: Daniel Arranz

Name and address of the factories:
Additional information:

Models / type references covered by this Certificate:

	Type: 230 50	Type: 230/400 50
Model (s)	SILEN I 33 8M, SILEN I 50 12 M, SILEN I 100 15M, SILEN S 60 12M, SILEN S 75 15M, SILEN S 100 18M, SILEN S 150 22M, SILEN S2 75 18M, SILEN S2 100 24M, SILEN S2 150 29M, SILEN S2 200 31 M, SILEN S2 300 36M NOX 25 6M, NOX 33 8M, NOX 100 150M NOX 75 15M, NOX 100 18M, NOX 150 22M	SILEN S 60 12, SILEN S 75 15, SILEN S 100 18, SILEN S 150 22 SILEN S2 75 18, SILEN S2 100 24, SILEN S2 150 29, SILEN S2 200 31 SILEN S2 300 36
Rated voltage	230 VAC 50Hz	230/400 3AC 50Hz
Rated power	200 W – 2800 W	900 W – 2600 W
Protection class	I	I
Protection degree	X5	X5
Medium temperature	40	40
Throughput capacity	(18-900) l/min	(18-900) l/min
Minimum height	0,7 m – 10 m	2 m – 10 m
Maximum height	0,7 m – 50 m	11 m – 50 m

	Type: 220 60	Type: 220/440 60
Model (s)	SILEN I 33 8M, SILEN I 50 12 M, SILEN I 100 15M, SILEN S 60 12M, SILEN S 75 15M, SILEN S 100 18M, SILEN S 150 22M, SILEN S2 75 18M, SILEN S2 100 24M, SILEN S2 150 29M, SILEN S2 200 31 M, SILEN S2 300 36M	SILEN S 60 12, SILEN S 75 15, SILEN S 100 18, SILEN S 150 22 SILEN S2 75 18, SILEN S2 100 24, SILEN S2 150 29, SILEN S2 200 31 SILEN S2 300 36
Rated voltage	220 VAC 60Hz	220/440 3AC 60Hz
Rated power	500 W – 2700 W	800 W – 2700 W
Protection class	I	I
Protection degree	X5	X5
Medium temperature	40	40
Throughput capacity	(25-1075) l/min	(150-1200) l/min
Minimum height	1 m – 15 m	5 m – 6 m
Maximum height	10 m – 55 m	14 m – 20 m

	Type: 230-50		Type: 220-230 60
Model (s)	SIROCCO 25 6M, SIROCCO 50 12M, SIROCCO 100 15M, SIROCCO 75 15M, SIROCCO 100 18M, SIROCCO 150 22M	Model (s)	SILEN I 33 8M, SILEN I 50 12 M, SILEN I 100 15M, SILEN S 60 12M, SILEN S 75 15M, SILEN S 100 18M, SILEN S 150 22M, SILEN S2 75 18M, SILEN S2 100 24M, SILEN S2 150 29M, SILEN S2 200 31 M, SILEN S2 300 36M
Rated voltage	230VAC 50Hz	Rated voltage	220-230 VAC 60Hz
Rated power	180W - 1100W	Rated power	500 W – 2700 W
Protection class	F	Protection class	I
Protection degree	X5	Protection degree	X5
Medium temperature	40	Medium temperature	40
Throughput capacity	(120-600) l/min	Throughput capacity	(25-1075) l/min
Minimum height	0,7 m – 18 m	Minimum height	1 m – 15 m
Maximum height	0,7 m – 50 m	Maximum height	10 m – 55 m

	Type 230 50	Type: 230/400 50
Model (s)	REPOSPool 100 18M 230 50 014977/STD	REPOSPool 100 18 230/400 50 014977/STD,
Rated voltage	230 VAC 50Hz	230/400 3AC 50Hz
Rated power	1100	1100
Protection class	I	I
Protection degree	IPX5	IPX5
Medium temperature	40	40
Throughput capacity	(150-350) l/min	(150-350) l/min
Minimum height	0	0
Maximum height	16	16

SGS Belgium NV - Division SGS CEBEC
Riverside Business Park
Avenue Internationalelaan 55, Building A
B-1070 Brussels, Belgium




Date: 15/10/2026

Signature: Daniel Arranz